10.4" Fanless Panel PC

Feature :

Intel Atom / VIA solution, Fanless, Touch screen, Water Proof, Open-frame design, LED Backlight Panel

Application:

Information Kiosk, POS, Mobile solution, Automation control

Panel PC Information

LCD Panel	AUO	CMO
Resolution	SVGA 800 x 600	XGA 1024 x 768
Brightness (cd/m2)	400	
Contrast Ratio	700 : 1	
Backlight	LED / CCFL	
Number of Colors	262144	
Touch Screen	AMT 8 wires / Resistive touch screen	
Mounting Spec.	VESA 75/100 / Panel Mount	
Panel frame water proof	IP65	
Webcam (Option)	5.0 Mega pixel - auto focus	
Accessory (Option)	Wall Mount Kit / Stand	

Fanless Panel PC :

. Panel PC Dimension	67.9 H x 287.6 W x 245 D mm (For Lex STD M/B)
	60.9 H x 287.6 W x 245 D mm (For 3.5" M/B)
	67.9 H x 287.6 W x 245 D mm Special App.(BI525C)
. Case Dimension	55.9 H x 258.6 W x 218 D mm (For Lex STD M/B)
	48.9 H x 258.6 W x 218 D mm (For 3.5" M/B)
. Front Panel Dimension	12 H x 287.6 W x 245 D mm
. Material	Plastics front frame + Aluminum
. Weight	2.2 Kg
. Storage Space	2.5" HDD
. Operation Humidity	5 ~ 90% @ 39 C, non-condensing

M/B information: (Please refer to M/B specification)

CPU Type	M/B Model	VGA	COM	LAN	USB	Audio	KB/MS	Others	Operation Temp.	
									CF Card	HDD
Intel Atom D525	3I525CW	1	4	2	2	YES	-	-	55°C	50°C
	BI525CW	1	4	2	2	YES	-	Rechargeable Battery	-	-
Intel Atom N270	3I270C	-	4	1	2	YES	-	-	50°C	45°C
	CI270CW	1	5	2	4	YES	YES	DVI	55°C	50°C
	MI270AW	1	2	2	4	YES	YES	DVI / TV-Out / Video-In	55°C	50°C
VIA Eden / ULV or C7	3V700C	1	3	1	2	YES	-	–	50°C	45°C

More Functions				
Aluminum / Stainless Case		Capacitive touch	Webcam	Parallel Port
DC +6V to +36V	High Brightness Panel	1 ~ 4 Video-IN	Bluetooth	Optional LAN
Rechargeable Battery	DIO	Speaker	Wi-Fi	GPS
3G	4 x COM	H.264 decode	USB	

The above available functions outline the possibility with system, for more information please contact us.

Dimension



CI270C



MI270A



3I270C

3I525C/W