



MT8102iE



MT8073iE



MT8053iE



MT8150XE



MT8051iP



MT8071iP



MT8102iP



MT8121XE3

Performance, Design, and Versatility

MT8000iE · XE · iP Series




Ultra-slim form factor

Enables HMI can be installed in any industrial control environment.



Dual Ethernet ports

Dual Ethernet ports offers you to set up WAN/LAN or two different LAN/LAN network configurations. (MT8073iE/ MT8053iE)




Power isolation protection

Effectively avoids surges and ensures the reliability of HMI. (MT8050iE/ MT8053iE/ MT8071iE/ MT8073iE/ MT8102iE)

iE Series

iE Series, easily installed in any industrial control environment

- Ultra-slim form factor and new color design.
- Isolated RS-485 and PCB coating protections.




Power isolation protection

Effectively avoids surges and ensures the reliability of HMI.



Silver side

Elegant silver side and streamlined styling form factor shows aesthetic sense. (MT8090XE/ MT8092XE)



Wide viewing angle

Up to 89° wide viewing angle makes HMI monitoring less limited. (MT8121XE3/ MT8150XE)

XE Series

XE Series, optimal for industrial control application in various harsh environments

- 9.7" high-resolution (1024 x 768 pixels) HMI.
- 12" /15" large sizes of HMIs.
- Isolated RS-485, PCB coating, and power isolation protections.



Advanced Visualization

16.7-million colors display.

High Resolution

MT8102iP features a high-resolution 1024 x 600 LCD, and wide viewing angle (T: 70° / B: 70° / L: 80° / R: 80°).



10.1" MT8102iP

7" MT8071iP / MT8071iP2

4.3" MT8051iP



iP Series

New Choice, Unprecedented Experience!

- 10.1" high resolution LCD (1024 x 600 pixels) and 16.7M colors display.
- Supports for more than 300 different brands of PLC and controllers.

The Comparison of Software Features Between Different Models



Software Feature			
	iE Series	XE Series	iP Series
Project & Firmware Size Limit	22.5MB	64MB	22.5MB
History Size Limit	16MB	64/ 120MB	16MB
Project Protection	●	●	●
USB Cable Download		MT8121XE3 MT8150XE	
Pictures/Shape Library Embedded in Project	●	●	●
PLC TAG Embedded in Project	●	●	●
e-Mail	●	●	
Enhanced Security Mode	●	●	●
VNC Server	●	●	●
CAN Bus		MT8092XE	
Circular Trend Display	●	●	●
Combo Button	●	●	●
Media Player		●	
MQTT(Publisher / Subscriber)	●	●	
Operation Log	●	●	●
OPC UA Client	●	●	●
Picture Viewer	●	●	●
Recipe Database / Recipe View	●	●	●
USB Camera		●	
IP Camera		●	
VNC Viewer	●	●	
Watchdog	●	●	●
EasyAccess 2.0	Optional MT8053iE/MT8073iE Built-in License	Optional MT8092XE Built-in License	Optional

iE Series : MT8050iE, MT8053iE, MT8070iE, MT8071iE, MT8073iE, MT8102iE

XE Series : MT8090XE, MT8092XE, MT8121XE3, MT8150XE

iP Series : MT8051iP, MT8071iP, MT8071iP2, MT8102iP

* The iP Series models have to be programmed with EasyBuilder Pro V6.05.02 or later versions to apply the said functions.

* Note: The MT8102iP's OS version must be 20201007 or later versions.



	Model	MT8050iE	MT8053iE	MT8070iE	MT8071iE	MT8073iE	MT8102iE
Display	Display	4.3" TFT		7" TFT		7" TFT	
	Resolution	480 x 272		800 x 480		800 x 480	
	Brightness (cd/ m ²)	400		400		400	
	Contrast Ratio	500: 1		800: 1		800: 1	
	Backlight Type	LED		LED		LED	
	Backlight Life Time	> 30,000 hrs.		> 30,000 hrs.		> 30,000 hrs.	
	Colors	16.7M		16.7M		16.7M	
	LCD Viewing Angle (T/B/L/R)	50/70/70/70		80/60/80/80		80/60/80/80	
	Pixel Pitch (mm)	0.198(H) x 0.198(V)		0.1926(H) x 0.179(V)		0.1926(H) x 0.179(V)	
Touch Panel	Type	4-wire Resistive Type		4-wire Resistive Type		4-wire Resistive Type	
	Accuracy	Active Area Length(X)±2%, Width(Y)±2%		Active Area Length(X)±2%, Width(Y)±2%		Active Area Length(X)±2%, Width(Y)±2%	
Memory	Flash	128 MB		128 MB		128 MB	
	RAM	128 MB		128 MB		128 MB	
Processor		32-bit RISC 600MHz		32-bit RISC 600MHz		32-bit RISC 600MHz	
I/O Port	USB Host	USB 2.0 x 1		USB 2.0 x 1		USB 2.0 x 1	
	Ethernet	10/100 Base-T x 1	LAN 1: 10/100/1000 Base-T x 1 LAN 2: 10/100 Base-T x 1	10/100 Base-T x 1		10/100/1000 Base-T x 2	
	COM Port	COM1: RS-232/RS-485 2W/4W COM3: RS-485 2W		COM1: RS-232/RS-485 2W/4W COM3: RS-485 2W	COM1: RS-232 COM2: RS-485 2W/4W COM3: RS-485 2W	COM1: RS-232 COM2: RS-485 2W/4W COM3: RS-232/RS-485 2W*2	Con.A: COM1 RS-485 2W, COM2 RS-485 2W/4W, COM3 RS-485 2W/4W*1 Con.B: COM1 RS-232 / COM3 RS-232*2
	RS-485 Dual Isolation	N/A		Yes	N/A	N/A	N/A
	RTC	Built-in		Built-in		Built-in	
Power	Input Power	24±20%VDC	22~28VDC	24±20%VDC		24±20%VDC	
	Power Isolation	Built-in		N/A		Built-in	
	Power Consumption	400mA@24VDC	450mA@24VDC	350mA@24VDC	450mA@24VDC	600mA@24VDC	
	Voltage Resistance	500VAC (1 min.)		500VAC (1 min.)		500VAC (1 min.)	
	Isolation Resistance	Exceed 50MΩ @ 500VDC		Exceed 50MΩ @ 500VDC		Exceed 50MΩ @ 500VDC	
	Vibration Endurance	10 to 25Hz (X, Y, Z direction 2G 30 minutes)		10 to 25Hz (X, Y, Z direction 2G 30 minutes)		10 to 25Hz (X, Y, Z direction 2G 30 minutes)	
	PCB Coating	Yes		Yes		Yes	
Specification	Enclosure	Plastic		Plastic		Plastic	
	Dimensions WxHxD	128 x 102 x 32 mm		200.3 x 146.3 x 34 mm		200.3 x 146.3 x 34 mm	
	Panel Cutout	119 x 93 mm		192 x 138 mm		192 x 138 mm	
	Weight	Approx. 0.25 kg		Approx. 0.6 kg		Approx. 0.6 kg	
	Mount	Panel mount		Panel mount		Panel mount	
	Protection Structure	UL Type 4X (indoor use only) / NEMA4 / IP65 Compliant Front Panel		UL Type 4X (indoor use only) / NEMA4 / IP65 Compliant Front Panel		UL Type 4X (indoor use only) / NEMA4 / IP65 Compliant Front Panel	
	Storage Temperature	-20° ~ 60° C (-4° ~ 140° F)		-20° ~ 60° C (-4° ~ 140° F)		-20° ~ 60° C (-4° ~ 140° F)	
Operating Temperature	0° ~ 50° C (32° ~ 122° F)		0° ~ 45° C (32° ~ 113° F)		0° ~ 50° C (32° ~ 122° F)		
Relative Humidity	10% ~ 90% (non-condensing)		10% ~ 90% (non-condensing)		10% ~ 90% (non-condensing)		
Certificate	CE	CE marked		CE marked		CE marked	
	UL	cULus Listed		cULus Listed		cULus Listed	
	ATEX	N/A		N/A	ATEX Zone 2/22 Category 3 G/D	ATEX Zone 2/22 Category 3 G/D	
Software		EasyBuilder Pro EasyAccess 2.0 (Optional)	EasyBuilder Pro Built-in EasyAccess 2.0	EasyBuilder Pro EasyAccess 2.0 (Optional)	EasyBuilder Pro Built-in EasyAccess 2.0	EasyBuilder Pro EasyAccess 2.0 (Optional)	EasyBuilder Pro EasyAccess 2.0 (Optional)

*1 MT8102iE: COM3 RS-485 4W will not be available when COM1 RS-485 2W is used.

*2 MT8073iE/ MT8102iE: Only Tx & Rx (no RTS/CTS) may be used for COM1 RS-232 when COM3 RS-232 is also used.

*3 MT8102iE: For customers who require UL, please order MT8102iEU. (MT8102iE is not UL listed.)

XE Series



Model		MT8090XE	MT8092XE	MT8121XE3	MT8150XE
Display	Display	9.7" TFT	9.7" TFT	12.1" IPS	15" IPS
	Resolution	1024 x 768	1024 x 768	1024 x 768	1024 x 768
	Brightness (cd/ m²)	350	350	500	400
	Contrast Ratio	500: 1	500: 1	1000: 1	1000: 1
	Backlight Type	LED	LED	LED	LED
	Backlight Life Time	> 30,000 hrs.	> 30,000 hrs.	> 30,000 hrs.	> 50,000 hrs.
	Colors	262K	262K	16.7M	16.2M
	LCD Viewing Angle (T/B/L/R)	60/70/70/70	60/70/70/70	89/89/89/89	89/89/89/89
	Pixel Pitch (mm)	0.192(H) x 0.192(V)	0.192(H) x 0.192(V)	0.24(H) x 0.24(V)	0.297(H) x 0.297(V)
	Touch Panel	Type	4-wire Resistive Type	4-wire Resistive Type	4-wire Resistive Type
Accuracy		Active Area Length(X)±2%, Width(Y)±2%	Active Area Length(X)±2%, Width(Y)±2%	Active Area Length(X)±2%, Width(Y)±2%	Active Area Length(X)±2%, Width(Y)±2%
Memory	Flash	512 MB	512 MB	256 MB	256 MB
	RAM	256 MB	256 MB	256 MB	256 MB
Processor		32-bit RISC 1GHz	32-bit RISC 1GHz	32-bit RISC 1GHz	32-bit RISC 1GHz
I/O Port	SD Card Slot	N/A	N/A	SD/SDHC	SD/SDHC
	USB Host	USB 2.0 x 1	USB 2.0 x 1	USB 2.0 x 1	USB 2.0 x 1
	USB Client	N/A	N/A	USB 2.0 x 1	USB 2.0 x 1
	Ethernet	10/100/1000 Base-T x 1	10/100/1000 Base-T x 2	10/100 Base-T x 1	10/100 Base-T x 1
	COM Port	Con.A: COM2 RS-485 2W/4W, COM3 RS-485 2W Con.B: COM1 RS-232	Con.A: COM2 RS-485 2W/4W, COM3 RS-485 2W Con.B: COM1 RS-232, COM3 RS-232*	COM1: RS-232/RS-485 2W/4W, COM3: RS-485 2W	COM1: RS-232/RS-485 2W/4W, COM3: RS-485 2W
	RS-485 Dual Isolation	N/A	N/A	Yes	Yes
	CAN Bus	N/A	Yes	N/A	N/A
	Audio Output	N/A (Supports USB Audio)	N/A (Supports USB Audio)	N/A (Supports USB Audio)	N/A (Supports USB Audio)
	RTC		Built-in	Built-in	Built-in
	Power	Input Power	24±20%VDC	24±20%VDC	24±20%VDC
Power Isolation		Built-in	Built-in	Built-in	Built-in
Power Consumption		650mA@24VDC	650mA@24VDC	1.5A@24VDC	1.2A@24VDC
Voltage Resistance		500VAC (1 min.)	500VAC (1 min.)	500VAC (1 min.)	500VAC (1 min.)
Isolation Resistance		Exceed 50MΩ @ 500VDC	Exceed 50MΩ @ 500VDC	Exceed 50MΩ @ 500VDC	Exceed 50MΩ @ 500VDC
Vibration Endurance		10 to 25Hz (X, Y, Z direction 2G 30 minutes)	10 to 25Hz (X, Y, Z direction 2G 30 minutes)	10 to 25Hz (X, Y, Z direction 2G 30 minutes)	10 to 25Hz (X, Y, Z direction 2G 30 minutes)
Specification	PCB Coating	Yes	Yes	Yes	Yes
	Enclosure	Plastic	Plastic	Plastic	Aluminum
	Dimensions WxHxD	260.6 x 203.1 x 36.5 mm	260.6 x 203.1 x 36.5 mm	317 x 243 x 41 mm	366 x 293 x 57 mm
	Panel Cutout	250 x 192 mm	250 x 192 mm	305 x 231 mm	352 x 279 mm
	Weight	Approx. 0.85 kg	Approx. 0.85 kg	Approx. 1.7 kg	Approx. 2.75 kg
	Mount	Panel mount, VESA mount 75 x 75 mm	Panel mount, VESA mount 75 x 75 mm	Panel mount, VESA mount 75 x 75 mm	Panel mount, VESA mount 75 x 75 mm
Environment	Protection Structure	NEMA4 / IP65 Compliant Front Panel	UL Type 4X (indoor use only) / NEMA4 / IP65 Compliant Front Panel	NEMA4 / IP65 Compliant Front Panel	UL Type 4X (indoor use only) / NEMA4 / IP65 Compliant Front Panel
	Storage Temperature	-20° ~ 60° C (-4° ~ 140° F)	-20° ~ 60° C (-4° ~ 140° F)	-20° ~ 60° C (-4° ~ 140° F)	-20° ~ 60° C (-4° ~ 140° F)
	Operating Temperature	0° ~ 50° C (32° ~ 122° F)	0° ~ 50° C (32° ~ 122° F)	0° ~ 50° C (32° ~ 122° F)	0° ~ 50° C (32° ~ 122° F)
	Relative Humidity	10% ~ 90% (non-condensing)	10% ~ 90% (non-condensing)	10% ~ 90% (non-condensing)	10% ~ 90% (non-condensing)
Certificate	CE	CE marked	CE marked	CE marked	CE marked
	UL	N/A	cULus Listed	N/A	cULus Listed
	ATEX	ATEX Zone 2/22 Category 3 G/D	ATEX Zone 2/22 Category 3 G/D	N/A	ATEX Zone 2/22 Category 3 G/D
Software		EasyBuilder Pro EasyAccess 2.0 (Optional)	EasyBuilder Pro Built-in EasyAccess 2.0	EasyBuilder Pro EasyAccess 2.0 (Optional)	EasyBuilder Pro EasyAccess 2.0 (Optional)

* MT8092XE: Only Tx & Rx (no RTS/CTS) may be used for COM1 RS-232 when COM3 RS-232 is also used.

iP Series



Model		MT8051iP	MT8071iP	MT8071iP2	MT8102iP
Display	Display	4.3" TFT	7" TFT	7" TFT	10.1" TFT
	Resolution	480 x 272	800 x 480	800 x 480	1024 x 600
	Brightness (cd/ m ²)	400	300	300	350
	Contrast Ratio	500: 1	500: 1	500: 1	500: 1
	Backlight Type	LED	LED	LED	LED
	Backlight Life Time	>30,000 hrs.	>30,000 hrs.	>30,000 hrs.	50,000 hrs.
	Colors	16.7M	16.7M	16.7M	16.7M
	LCD Viewing Angle (T/B/L/R)	50/70/70/70	70/50/70/70	70/50/70/70	70/70/80/80
	Pixel Pitch (mm)	0.198(H) x 0.198(V)	0.1926(H) x 0.179(V)	0.1926(H) x 0.179(V)	0.2175(H) x 0.2088(V)
Touch Panel	Type	4-wire Resistive Type	4-wire Resistive Type	4-wire Resistive Type	4-wire Resistive Type
	Accuracy	Active Area Length(X)±2%, Width(Y)±2%	Active Area Length(X)±2%, Width(Y)±2%	Active Area Length(X)±2%, Width(Y)±2%	Active Area Length(X)±2%, Width(Y)±2%
Memory	Flash	128 MB	128 MB	128 MB	128 MB
	RAM	128 MB	128 MB	128 MB	128 MB
Processor		32-bit RISC 600MHz	32-bit RISC 600MHz	32-bit RISC 528MHz	32-bit RISC 528MHz
I/O Port	USB Host	USB 2.0 x 1	USB 2.0 x 1	USB 2.0 x 1	USB 2.0 x 1
	Ethernet	10/100 Base-T x 1	10/100 Base-T x 1	10/100 Base-T x 1	10/100 Base-T x 1
	COM Port	COM1: RS-232/RS-485 2W/4W COM3: RS-485 2W	COM1: RS-232 4W, COM2: RS-485 2W/4W	COM1: RS-232 4W, COM2: RS-485 2W/4W Mark/Space parity mode is not supported.	Con.A: COM2 RS-485 2W/4W, COM3 RS-485 2W Con.B: COM1 RS-232 4W, COM3 RS-232 2W*
RTC		Built-in (CR2032 3V lithium battery.)	Built-in	Built-in	Built-in
Power	Input Power	10.5~28VDC	10.5~28VDC	10.5~28VDC	10.5~28VDC
	Power Isolation	Built-in	Built-in	Built-in	Built-in
	Power Consumption	800mA@12VDC ; 400mA@24VDC	1A@12VDC ; 500mA@24VDC	1A@12VDC ; 450mA@24VDC	1.3A@12VDC ; 650mA@24VDC
	Voltage Resistance	500VAC (1 min.)	500VAC (1 min.)	500VAC (1 min.)	500VAC (1 min.)
	Isolation Resistance	Exceed 50MΩ @ 500VDC	Exceed 50MΩ @ 500VDC	Exceed 50MΩ @ 500VDC	Exceed 50MΩ @ 500VDC
	Vibration Endurance	10 to 25Hz (X, Y, Z direction 2G 30 minutes)	10 to 25Hz (X, Y, Z direction 2G 30 minutes)	10 to 25Hz (X, Y, Z direction 2G 30 minutes)	10 to 25Hz (X, Y, Z direction 2G 30 minutes)
Specification	Enclosure	Plastic	Plastic	Plastic	Plastic
	Dimensions WxHxD	128 x 102 x 32 mm	200.4 x 146.5 x 34 mm	200.4 x 146.5 x 34 mm	271 x 213 x 36.4 mm
	Panel Cutout	119 x 93 mm	192 x 138 mm	192 x 138 mm	260 x 202 mm
	Weight	Approx. 0.25 kg	Approx. 0.52 kg	Approx. 0.52 kg	Approx. 1 kg
	Mount	Panel mount	Panel mount	Panel mount	Panel mount
Environment	Protection Structure	NEMA4 / IP65 Compliant Front Panel	NEMA4 / IP65 Compliant Front Panel	NEMA4 / IP65 Compliant Front Panel	NEMA4 / IP65 Compliant Front Panel
	Storage Temperature	-20° ~ 60° C (-4° ~ 140° F)	-20° ~ 60° C (-4° ~ 140° F)	-20° ~ 60° C (-4° ~ 140° F)	-20° ~ 60° C (-4° ~ 140° F)
	Operating Temperature	0° ~ 50° C (32° ~ 122° F)	0° ~ 50° C (32° ~ 122° F)	0° ~ 50° C (32° ~ 122° F)	0° ~ 50° C (32° ~ 122° F)
	Relative Humidity	10% ~ 90% (non-condensing)	10% ~ 90% (non-condensing)	10% ~ 90% (non-condensing)	10% ~ 90% (non-condensing)
Certificate	CE	CE marked	CE marked	CE marked	CE marked
Software		EasyBuilder Pro EasyAccess 2.0 (Optional)	EasyBuilder Pro EasyAccess 2.0 (Optional)	EasyBuilder Pro EasyAccess 2.0 (Optional)	EasyBuilder Pro EasyAccess 2.0 (Optional)

* MT8102iP: Only Tx & Rx (no RTS/CTS) may be used for COM1 RS-232 when COM3 RS-232 is also used.

The Product's colors printed in this brochure may differ from those of the actual product.

All information contained in this brochure is subject to change without notice.

Other company names and product names in this document are the trademarks or registered trademarks of their respective companies.



WEINTEK

Taiwan

Tel: +886-2-22286770
Fax: +886-2-22286771

Address: 14F., No. 13, Qiaohe Rd., Zhonghe Dist.,
New Taipei City 235029, Taiwan (R.O.C.)

Website: www.weintek.com
Sales: salesmail@weintek.com
Product Support: servicemail@weintek.com

    **RoHS** ISO 9001:2015

ENG / 2021.09.10