


DN-37/DN-37-A/DN-37-381/DN-37-381-A

I/O Connector Block with DIN-Rail Mounting and 37-pin D-sub Connector



Model: DN-37/DN-37-A




Model: DN-37-381/DN-37-381A

Functional Description


DN-37/DN-37-A

- I/O Connector Block with DIN-Rail Mounting
- Two 37-pin D-sub connector (One for expansion)
- Pin to Pin screw terminal for I/O connected
- Pitch : 5.08 m/m
- Dimension : 148mm x 76mm
- Current rating:1 A Max.
- Dielectric withstanding voltage: 250VAC for 1 minute
- DC rating: 50 V Max.



DN-37-381

- I/O Connector Block with DIN-Rail Mounting
- Two 19-pin header
- Pin to Pin screw terminal for I/O connected
- Pitch : 381mm(0.150inch)
- Dimension : 103mm x 86mm



Ordering Information

DN-37 Series	
DN-37 CR	I/O Connector Block (Pitch= 5.08 mm) with DIN-Rail Mounting and D-sub 37-pin connector (RoHS) Include one CA-3710 (37-pin Male-Male D-sub cable 1.0 M)
DN-37/2 CR	I/O Connector Block (Pitch= 5.08 mm) with DIN-Rail Mounting and D-sub 37-pin connector (RoHS) Include one CA-3720 (37-pin Male-Male D-sub cable 2.0 M)
DN-37/N CR	DN-37 without DIN-Rail Mount (RoHS)
DN-37-A Series	
DN-37-A CR	I/O Connector Block (Pitch= 5.08 mm) with DIN-Rail Mounting and Dsub 37-pin connector (RoHS) Include one CA-3710A (37-pin Male-Female D-sub cable 1.0M)
DN-37/N-A CR	DN-37-A without DIN-Rail Mount (RoHS)
DN-37-AM/2 CR	I/O Connector Block (Pitch= 5.08 mm) with DIN-Rail Mounting and D-sub 37-pin connector (RoHS) Include one CA-3720AM (37-pin Male-Female D-sub cable 2 M)
DN-37-A Series	
DN-37-381 CR	I/O Connector Block (Pitch=3.81 mm) with DIN-Rail Mounting and and D-sub 37-pin connector (RoHS) Include one CA-3710 (37-pin Male-Male D-sub cable 1.0 M)
DN-37-381-A CR	I/O Connector Block (Pitch= 3.81 mm) with DIN-Rail Mounting and and D-sub 37-pin connector (RoHS) Include one CA-3710A (37-pin Male-Female D-sub cable 1.0 M)

Accessories

CA-3710	Male-Male D-sub cable 1M (45°)
---------	--------------------------------

